

Threadseal Tape

Maximum Density, Highest Quality



**Color Coded for
Easy Identification**

White Sealing Tape



Our white sealing tape comes in a grade that will fit your budget!

- **CHEMICALLY RESISTANT**
- **OPERATES FROM -450°F to +450°F**
- **AVAILABLE IN 1/2" TO 1" SIZES**

Low Density

Medium Density

High Density

Economy Seal	Quality Seal	Industrial Seal
---------------------	---------------------	------------------------

0.35 g/cm³

0.7 g/cm³

1.5 g/cm³

Pink Industrial Sealing Tape

The Pink Advantage...

- **Manufactured to a higher density.**
- **Provides an impenetrable barrier to liquids & gases.**
- **Suitable for a wide temperature range (-450°F to +500°F).**
- **Suitable for metal pipes and fittings.**
- **Will not string or shred in use.**
- **Requires fewer wraps to seal.**

The Pink Size...

Width	Length	Pack Qty
1/4 in / 6.4 mm	260 in / 6.5 m	10
1/2 in / 12.6 mm	540 in / 13m	10
1/2 in / 12.6mm	1429in/36m	36
3/4 in / 19 mm	540 in / 13m	6
1.0 in / 25.4 mm	540 in / 13 m	6

Material	100% Virgin PTFE
Thickness	.003 in / .076 mm
Density	1.5 g/cm³
Color	Pink
PSI Rating	10,000 psi
Shelf Life	Indefinite



Developed specially for plumbers and pipe fitters!

Yellow Gas Sealing Tape



Developed specially for the petroleum, LPG, & natural gas industries!

Material	100% Virgin PTFE
Thickness	.004 in / .102 mm
Density	1.5 g/cm³
Color	Yellow
PSI Rating	300-4000 psi*
Shelf Life	Indefinite

*Depending on the certification.

The Yellow Size...

Width	Length	Pack Qty
½ in / 12.6 mm	260 in / 6.5 m	10
½ in / 12.6 mm	1182 in / 30 m	36
¾ in / 19 mm	260 in / 6.5 m	6
1.0 in / 25.4 mm	260 in / 6.5 m	6

The Yellow Advantage...

- Manufactured to the highest density.
- Provides an impenetrable barrier to gases.
- Suitable for a wide temperature range (-450°F to +500°F).
- Suitable for metal pipes and fittings.
- Certified by CSA (USA & Canada) & Underwriters Laboratory.
- Will not string or shred in use.
- Requires fewer wraps to seal.

Green Oxygen Sealing Tape

The Green Advantage...

- “Degreased” to enhance safety.
- Manufactured to the highest density.
- Provides an impenetrable barrier to gases.
- Suitable for a wide temperature range (-450°F to +500°F).
- Suitable for degreased pipes and fittings.
- Will not string or shred in use.
- Requires fewer wraps to seal.

The Green Size...

Width	Length	Pack Qty
¼ in / 6.4 mm	260 in / 6.5 m	10
¼ in / 6.4 mm	480 in / 12.2 m	10
½ in / 12.6 mm	260 in / 6.5 m	10
½ in / 12.6 mm	480 in / 12.2 m	10
¾ in / 19 mm	260 in / 6.5 m	6
1.0 in / 25.4 mm	260 in / 6.5 m	6

Material	100% Virgin PTFE
Thickness	.004 in / .102 mm
Density	1.5 g/cm³
Color	Green
PSI Rating	2,000 psi
Shelf Life	Indefinite



Developed specially for oxygen use, but it is also useful for other gases!

Stainless Steel Thread Sealing Tape



Developed specially for installations using stainless steel pipe lines!

Material	PTFE & NICKEL
Thickness	.004 in / .102 mm
Density	1.6 g/cm³
Color	Silver
PSI Rating	10,000 psi
Shelf Life	Indefinite

The Stainless Steel Size...

Width	Length	Pack Qty
¼ in / 6.4 mm	260 in / 6.5 m	10
½ in / 12.6 mm	260 in / 6.5 m	10
¾ in / 19 mm	260 in / 6.5 m	6
1.0 in / 25.4 mm	260 in / 6.5 m	6

The Stainless Steel Advantage...

- Impregnated with nickel powder to prevent galling or seizing.
- Manufactured to the highest density.
- Provides an impenetrable barrier to gases.
- Suitable for a wide temperature range (-450°F to +500°F).
- Suitable for metal pipes and fittings.
- Will not string or shred in use.
- Requires fewer wraps to seal.

UNASCO Gold Sealing Tape

The Gold Advantage...

- Recommended for chemical application.
- Manufactured to the highest density.
- Provides an impenetrable barrier to gases.
- Suitable for a wide temperature range (-450°F to +500°F).
- Suitable for metal pipes and fittings.
- Will not string or shred in use.
- Requires fewest wraps to seal.

Material	100% Virgin PTFE
Thickness	.004 in / .102 mm
Density	1.6 g/cm³
Color	Gold
PSI Rating	10,000 psi
Shelf Life	Indefinite

The Gold Size...

Width	Length	Pack Qty
½ in / 12.6 mm	540 in / 13.5 m	10
½ in / 12.6 mm	1296 in / 32.5 m	10
¾ in / 19 mm	540 in / 13.5 m	6
1.0 in / 25.4 mm	540 in / 13.5 m	6



This premium quality tape is ideally suited to applications which demand exacting standards of reliability.