Page: 1 of 5

Issue Date: September 2015

ISSUED by UNASCO

Product Name GAS SEAL TAPE

| GHS Product<br>Identifier                                     | GAS SEAL TAPE   |  |
|---|---|--|
| Company Name  | UNASCO PTY LTD  | Emergency Telephone Number:  |
| Address   | 1 Amax Avenue<br>Girraween, NSW 2145 Australia                                  | Unasco Pty Ltd CCN710993<br>CHEMTREC: (USA & Canada): 800 424 9000 |
| Telephone/Fax<br>Number                                       | Non-Emergency Tel: 800 713 4589<br>Fax: 707 238 1419                            | International: 703 741 597   |
| Recommended use of<br>the chemical and<br>restrictions on use | Industrial tape.  |  |
| 2. Hazard Ide   | entification  |  |
| Classification of the substance or mixture                    | Not classified as Hazardous according t<br>of Classification and labeling of Ch |  |

| 3. Compositi                  | ion/information on ingredient                 | ts           |                   |
|-------------------------------|---|--------------|-------------------|
| Information on<br>Composition | This product contains<br>- Polytetrafluor     | -            | g ingredients:    |
| composition                   | - Distillates<br>- Pigment                    | (petroleum), | hydro-treated     |
| Ingredients                   | Name  | CAS          | <u>Proportion</u> |
|                               | Ingredients determined<br>not to be hazardous | d            | 100%              |

# 4. First-aid measures

| Inhalation                  | Not considered a potential route of exposure. However, if inhaled, remove      |
|-----------------------------|--|
|                             | affected person from contaminated area. Keep at rest until recovered. If       |
|                             | symptoms develop and/or persist seek medical attention.                        |
| Ingestion                   | Unlikely due to form of product. However, if ingested, do not induce           |
|                             | vomiting. Wash out mouth thoroughly with water. If symptoms develop seek       |
|                             | medical attention.   |
| Skin                        | Wash affected area thoroughly with soap and water. If symptoms develop         |
|                             | seek medical attention.  |
| Eye contact                 | Not considered a potential route of exposure. However if in eyes, hold eyelids |
| -                           | apart and flush the eyes continuously with running water. Continue flushing    |
|                             | for several minutes until all contaminants are washed out completely. If       |
|                             | symptoms develop and persist seek medical attention.                           |
| <b>First Aid Facilities</b> | Eyewash and normal washroom facilities.  |
| Advice to Doctor            | Treat symptomatically.   |
|                             | ficat Symptomatically.   |
| Other Information           |  |
|                             |  |

## 5. Fire-fighting measures

| Suitable                               | Use carbon dioxide, dry chemical or foam.  |
|--|--|
| extinguishing media                    |  |
| Hazards from                           | Under fire conditions this product may emit toxic and/or irritating fumes,   |
| Combustion                             | smoke and gases including carbon monoxide, carbon dioxide, hydrogen  |
| Products                               | fluoride and oxides of nitrogen.   |
| Specific hazards                       | Combustible. This product will readily burn under fire conditions.   |
| arising from the                       |  |
| chemical                               |  |
| Decomposition                          | Not available  |
| Temp.                                  |  |
| Precautions in<br>connection with Fire | Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to |
| connection with Fife                   | vapors or fumes. Water spray may be used to cool down heat-exposed   |

#### Page: 2 of 5

Issue Date: September 2015

ISSUED by UNASCO

Product Name GAS SEAL TAPE

containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

| 6. Accidental release measures  |   |  |
|---|---|--|
| Personal<br>precautions,<br>protective equipment<br>and emergency<br>procedures | Wear appropriate personal protective equipment and clothing to prevent<br>exposure. Collect the material and place into a suitable labeled container.<br>Dispose of waste according to the applicable local and national regulations.<br>If contamination of sewers or waterways occurs inform the local water and<br>waste management authorities in accordance with local regulations.  |  |
| 7. Handling a   | nd storage  |  |
| Precautions for Safe<br>Handling  | Avoid exposure. Use only in a well ventilated area. Keep containers tightly<br>closed. Prevent the build up of dusts, mists or vapors in the work<br>atmosphere. Maintain high standards of personal hygiene i.e. Washing hands<br>prior to eating, drinking, smoking or using toilet facilities.   |  |
| Conditions for safe<br>storage, including                                       | Store in a cool, dry, well-ventilated area, out of direct sunlight. Ensure that storage conditions comply with applicable local and national regulations.   |  |
| any incompatabilities<br>Handling<br>Temperatures                               | Recommended operating temperatures: -260°C (-436°F) to 260°C (500°F)  |  |
| Storage<br>Temperatures   | Store below 260°C(500°F).   |  |
| 8. Exposure c   | controls/personal protection  |  |
| Occupational<br>exposure limit values   | No exposure value assigned for this material However,<br>the available exposure limits for decomposition products are given below:  |  |
|   | SubstanceTWASTELNOTICESppm mg/m³ ppm mg/m³Hydrogen fluoride32.6Peak Limitation  |  |
|   | TWA (Time Weighted Average): The average airborne concentration of a<br>particular substance when calculated over a normal eight-hour working day,<br>for a five-day week.<br>STEL (Short Term Exposure Limit): The average airborne concentration over a<br>15 minute period which should not be exceeded at any time during a normal<br>eight-hour workday.<br>Peak Limitation: A ceiling concentration which should not be exceeded over<br>a measurement period which should be as short as possible but not exceeding<br>15 minutes. |  |
| Biological Limit<br>Values  | No biological limits allocated.   |  |
| Appropriate<br>engineering controls   | Use with good general ventilation.  |  |
| Respiratory<br>Protection   | None required, when used as intended.   |  |
| Eye Protection  | None required, when used as intended.   |  |
| Hand Protection   | None required, when used as intended.   |  |
| Body Protection   | Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended.  |  |

#### 9. Physical and chemical properties

| Appearance                   |                      |
|------------------------------|----------------------|
| Color                        | Solid polymeric film |
| Odor                         | Yellow               |
| Decomposition<br>Temperature | Odorless             |
|                              | Not available        |

# Safety Data Sheet

Page: 3 of 5

Issue Date: September 2015

ISSUED by UNASCO

Product Name GAS SEAL TAPE

| Melting Point                             | Not available     |
|---|-------------------|
| <b>Boiling Point</b>                      | Not available     |
| Solubility in Water                       | Insoluble         |
| Specific Gravity                          | 2.1               |
| РН  | Not applicable    |
| Vapor Pressure                            | Not applicable    |
| Vapor Density<br>(Air=1)                  | Not available     |
| <b>Evaporation Rate</b>                   | Not available     |
| Odor Threshold                            | Not available     |
| Viscosity                                 | Not applicable    |
| Partition Coefficient:<br>n-octanol/water | Not available     |
| Flash Point                               | Not applicable    |
| Flammability                              | Not flammable     |
| Auto-Ignition<br>Temperature              | Not self igniting |
| Explosion Limit -                         | Not applicable    |
| Upper<br>Explosion Limit -<br>Lower       | Not applicable    |

## 10. Stability and reactivity

| Reactivity                             | Reacts with incompatible materials.   |  |
|--|---|--|
| Chemical Stability                     | Stable under normal conditions of storage and handling.   |  |
| Conditions to Avoid                    | Heat and sources of ignition. Temperatures >260°C(500°F)<br>without   |  |
| Incompatible<br>Materials              | Strong oxidizing agents. Alkali metals, extremely potent oxidizers e.g.<br>fluorine, chlorine tri-fluoride, 80% NaOH or KOH, metal hydrides such as<br>boranes (e.g. B2H6) aluminum chloride, ammonia, certain amines (R-NH2)<br>imines (RH-NH) and 70% nitric acid at temperatures near 260°C (500°F). Do not<br>use on oxygen lines.  |  |
| Hazardous<br>Decomposition<br>Products | Thermal decomposition may result in the release of toxic and/or<br>irritating fumes including carbon monoxide, hydrogen fluoride and carbon<br>dioxide. Carbonyl fluoride is the main decomposition product formed when<br>PTFE is subjected to extended exposure at normal sintering temperatures<br>400°C(752°F). Carbonyl fluoride is immediately converted to highly<br>corrosive hydrogen fluoride in the presence of moist air. |  |
| Possibility of<br>hazardous reactions  | Reacts with incompatible materials.   |  |

#### 11. Toxicological Information

| Toxicology  | No toxicology data available for this product.   |
|-------------|--|
| Information |  |
|             | No toxicity was observed in male/female rats fed PTFE (up to 25%) for 90 days. Local sarcomas were induced in mice and rats implanted subcutaneously or intraperitoneally with PTFE. However, this is not considered relevant to normal industrial usage.            |
| Ingestion   | Ingestion unlikely due to form of product. Ingestion of this product may irritate the gastric tract causing nausea and vomiting.   |
| Inhalation  | No adverse effects expected. The material is not normally an inhalation hazard at temperatures below 260°C(500°F) as it remains an inert solid. However, exposure to   |
|             | thermal degradation products at temperatures above $260^{\circ}C(500^{\circ}F)$ or fumes from tobacco contaminated with particles of the product may result in polymer fume fever or influenza-like symptoms (chills, headaches, difficulty in breathing and fever). |
|             | Symptoms may appear several hours after exposure but will disappear within   |

## Page: 4 of 5

Issue Date: September 2015

Product Name GAS SEAL TAPE

| Skin                                    | 24-48 hours. There are exposure standards for decomposition products.<br>May be irritating to skin. The symptoms may include redness, itching and swelling.       |
|---|---|
| Eye                                     | Eye contact may cause mechanical irritation. May result in mild abrasion.   |
| Respiratory<br>sensitization            | Not expected to be a respiratory sensitizer.  |
| Skin Sensitization                      | Not expected to be a skin sensitizer.   |
| Germ cell<br>mutagenicity               | Not considered to be a mutagenic hazard.  |
| Carcinogenicity                         | Polytetrafluoroethylene is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). |
| Reproductive                            | Not considered to be toxic to reproduction.   |
| Toxicity STOT-<br>single exposure       | Not expected to cause toxicity to a specific target organ.  |
| STOT-repeated<br>exposure<br>Aspiration | Not expected to cause toxicity to a specific target organ.  |
| Hazard                                  | Not considered to be an aspiration hazard.  |

#### 12. Ecological information

| Ecotoxicity                   | No ecological data are available for this material.          |
|-------------------------------|--|
| Persistence and degradability | Not available  |
| Mobility                      | Not available  |
| Bioaccumulative               | Not available  |
| Potential<br>Other Adverse    | Not available  |
| Effects<br>Environmental      | Prevent this material entering waterways, drains and sewers. |
| Protection                    | revent this material entering waterways, dialns and sewers.  |

#### 13. Disposal considerations

| Disposal       | The disposal of the spilled or waste material must be done in accordance with |
|----------------|---|
| Considerations | applicable local and national regulations.                                    |

# 14. Transport information

| Transport                  | Road and Rail Transport   |
|----------------------------|---|
| Information                | Not classified as Dangerous Goods.  |
|                            | Marine Transport (IMO/IMDG):  |
|                            | Not classified as Dangerous Goods by the criteria of the International<br>Maritime Dangerous Goods Code (IMDG Code) for transport by sea.   |
|                            | Air Transport (ICAO/IATA):<br>Not classified as Dangerous Goods by the criteria of the International Air<br>Transport Association (IATA) Dangerous Goods Regulations for transport by<br>Air. |
| IMDG Marine                | Νο  |
| pollutant                  |   |
| 15. Regulatory information |   |
| Regulatory<br>Information  | Not classified as Hazardous according to the Globally Harmonized System of Classification and labeling of Chemicals (GHS).  |
|                            | Not classified as a Scheduled Poison according to the Standard for the<br>Uniform Scheduling of Medicines and Poisons (SUSMP).  |

ISSUED by UNASCO

# Safety Data Sheet

Page: 5 of 5

Issue Date: September 2015

ISSUED by UNASCO

Product Name GAS SEAL TAPE

16. Other Information